Fuse-link, high speed, 63 A, AC 690 V, DC 500 V, BS88, 19 x 77 mm, aR, BS $\,$



63FE

General specifications	
Product name	Eaton Bussmann series high speed British standard fuse
Part no.	63FE
EAN	5027590420594
Product Length/Depth	76 millimetre
Product height	20 millimetre
Product width	20 millimetre
Product weight	40.4 gram
Compliances	CE Marked RoHS Compliant
Certifications	UL Recognized IEC Rated Designed and tested to BS88 part 4 IEC 60269-4
Product Tradename	None
Product Type	High speed British standard fuse
Product Sub Type	None
Electrical data	
Amperage Rating	63 A
Voltage rating	690 V (IEC), 700 V (UL)
Rated voltage AC	690 V
Rated voltage DC	500 V
Interrupt rating	200 kA RMS Sym, 50 kA at 500 Vdc
Class	Class aR
Clearing (I2T)	480 at 415 V, 750 at 660 V
Watt losses	12 W
Product specifications	
Application	Semiconductor, DC Common bus, DC drives, power converters/rectifiers
Fuse indicator	None
Compatible Trip indicator/microswitch	
Suitable for	EC-600 Trip indicator kit (indicator + clips) T1700 Fuse indicator MAI Microswitch/adaptor MBI Microswitch/adaptor

Technical data ETIM 8.0

iconnical data Ellin 0.0		
Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation	n, device / Safety fuse i	nserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])
Fuse construction type according to IEC 60269		Other
Type of current		AC/DC
Rated voltage AC	V	690
Rated voltage DC	V	500
Rated current	Α	63
Utilization category		aR (accompanied semiconductor protection)
Breaking capacity	kA	200
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	12
Mounting holes		M6
Centre-to-centre distance of connections	mm	61.8