



Fuse-link, LV, 63 A, AC 690 V, 22 x 58 mm, gL/gG, IEC

**EL Number  
(Norway)**      **C22G63  
1664187**

Similar to illustration

Product name	Eaton Bussmann series low voltage cylindrical fuse
Part no.	CYLINDRICAL FUSE 22 x 58 63A GG 690V AC
EAN	5027590495523
Product Length/Depth	58 millimetre
Product height	22.2 millimetre
Product width	22.2 millimetre
Product weight	54.8 gram
Compliances	GoST-R CE Marked RoHS Compliant
Certifications	IEC 60269
Product Tradename	None
Product Type	Low voltage cylindrical fuse
Product Sub Type	None
Amperage Rating	63 A
Voltage rating	690 V
Voltage type	AC
Breaking capacity	80 kA
Utilization category	gL/gG (cable protection/equipment protection)
Suitable for	CH22 Modular fuse holder

### Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015])		
Model		Ceramic fuse
Size		22x58 mm
Voltage type		AC
Rated current	A	63
Rated voltage	V	690
Utilization category		gL/gG (cable protection/equipment protection)
Rated operating frequency	Hz	45 - 62
Type of fuse status indicator		Other
Release characteristic		Other
Breaking capacity	kA	80
Power loss at rated current	W	6.9