



Fuse-link, high speed, 25 A, AC 600 V, 10 x 38 mm, aR, UL

FWC-25A10F

Similar to illustration

General specifications		
Product name		Eaton Bussmann series high speed cylindrical fuse
Part no.		FWC-25A10F
EAN		5027590420600
Product Length/Depth		38 millimetre
Product height		11 millimetre
Product width		11 millimetre
Product weight		8.8 gram
Compliances		RoHS Compliant CE Marked
Certifications		CSA Certified UL Recognized
Product Tradename		None
Product Type		High speed cylindrical fuse
Product Sub Type		None
Electrical data		
Amperage Rating		25 A
Voltage rating		600 V
Voltage type		AC/DC
Interrupt rating		200 kAIC Vac
Class		Class aR
Clearing (I2T)		390
Product specifications		
Application		Semiconductor, DC Common bus, DC drives, Power converters/rectifiers
Fuse indicator		Other
Fuse size		10 x 38 mm
Compatible microswitch		
Accessories		CHM modular fuse holder BMM Fuse block

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss13-27-14-20-02 [AFZ797018])		
Model		Ceramic fuse
Size		10x38 mm
Voltage type		AC/DC
Rated current	A	25
Rated voltage	V	600
Utilization category		aR (accompanied semiconductor protection)
Rated operating frequency	Hz	45 - 62
Type of fuse status indicator		Other
Release characteristic		Other
Breaking capacity	kA	200
Power loss at rated current	W	6