Data Sheet



Coaxial Panel Connector 22_MMBX-50-0-1/111_N

Description

Straight bulkhead receptacle jack

Interface standards
SUHNER-MMBX



Technical Data

Electrical Data

 $\begin{array}{ll} \text{Impedance} & 50 \ \Omega \\ \text{Interface frequency max.} & 12.4 \ \text{GHz} \end{array}$

Mechanical Data

Chassis torque 2 Nm
Number of matings 100
Weight 0.0014 kg

Environmental Data

Operating temperature -55 °C to 155 °C 2011/65/EU (RoHS - including 2015/863 and 2017/2102) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	LCP (Liquid crystal polymer)	

Related Documents

Outline drawing DOU-00010456
Catalogue drawing DCA-00010458

Ordering Information

Single package 22_MMBX-50-0-1/111_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.